"B" or "Special" List.

13. S. H. Varadha Raj, care of The Manager, Gramasevalaya, French-Rocks.
14. N. Bylamuniyappa, Adi Jambava Street, Nelamangala.
15. K. M. Veeriah, Kakanur, Channagiri Taluk, Santhebennur Post.
16. A. Nanjiah, 131, Fourth Main Road, Chamarajpet, Bangalore City.
17. P. Padmanabha Naidu, 13, Joripet, Bangalore City.
18. H. Rangegowda, son of Mr. Hanume Gowda, Hanthanamore Village, Alur, Hassan District.
19. K. Venkataramappa, care of G. S. Bayanna, Village Munsiff, Gudibanda.
20. B. Yellappa, son of B. Manjappa, Compounder, Nagar, Hosanagar Taluk.
21. Ameer Ahamedulla Khan, 15, Sirse Road, Chamarajpet, Bangalore City.
22. V. M. Kuppaswamy Mudaliar, 47, Kalasipalyam, Bangalore.
23. P. T. Ramachandra, Mr. V. Thimmayya Pandit, Burganahatty, Chitaldrug.
24. K. N. Nagaraj, son of Narasamma, Milk Merchant, Fort, Kankanhalli.

By Order,
K. THIPPERUDRIAH,
*Secretary,*
*Central Recruitment Board.*

*ENGINEERING DEPARTMENT.*

## OFFICE OF THE ASSISTANT ENGINEER, KANVA PROJECT SUB-DIVISION, CHANNAPATNA.

*Notice dated 18th June* 1940.

Sealed tenders will be received in the Office of the Assistant Engineer, Kanva Project Sub-Division, Channapatna, upto 3 P.M. on the 5th of July 1940 for the supply of granite, burnt or raw, stone slabs of the dimensions noted (Dodballapur slabs).

(1) At the workspot near Ippemarada Doddi about 6½ miles from Channapatna Railway Station.

(2) Supply at Channapatna Railway Station.

Each tender must be accompanied by a Treasury chellan for earnest money of Rs. 100 in the first instance to the credit of "23. Irrigation Major" against the account of the Assistant Engineer or in cash. Final acceptance of the tender rests with the Superintending Engineer, Mysore Circle, Mysore. The tender will be accepted or rejected by him without giving any reason irrespective of its being high or low.

The successful tenderer will have to deposit another sum of Rs. 150 before starting the work.

The supply should commence from the 1st of August 1940. On the sealed covers it should be noted as "Tenders for the supply of slabs." All corrections in the tender should be initialled.

| Name of material | Per | Quantity |
|---|---|---|
| 1. Granite burnt or raw stone slabs should not be less than 6" thick and 2' wide. They should be in lengths not less than 6'. The thickness and the width must be uniform throughout. The surface must be very uniform requiring very little of dressing. Slabs with veins, cracks and rough surface will be rejected and they should be removed from the spot at the cost of the Contractor within a week's time from the date of order. | S.ft. | 40,000 to be supplied in 4 months at 10,000 S.ft. monthly in instalments. |

M. L. NARASIMHA SASTRI,
*Assistant Engineer.*